

TX station: 6xBkk2-v
Gain solid integration : disabled

Site Name: Labelitaly

General data of Antenna System

TX station	6xBkk2-v
Site Name	Labelitaly
System of coordinates	Geographic
Longitude	00°00'00.000"
Latitude	00°00'00.000"
Ground level a.s.l. (m)	100.0
Antenna system height (m)	50.0
Transmitter power(Watt)	1000.000
Carrier wave frequency (MHz)	200.000
Antenna system central frequency (MHz)	200.000
Antenna base diagrams type 1	LABEL ITALY-BKK_2V PANEL VHF WB
Antenna base diagrams type 2	-
Polarization (H/V/C/X)	V
Transmitting cable attenuation (dB)	0.0
Additional attenuations(dB)	0.0
Base diagrams sectors (T = All, F = Front)	T
Velocity factor of cables to Antennas (0÷1)	0.88
Coordinate System(C = cartesian, P = polar)	P
Mast side / diameter(cm):	10.0
Mast cross section (T/Q/C)	C
Structure rotation w.r.t. North (°)	0.0
Mast rotation w.r.t. North (°)	0.0

Information about antennas used in the System

	<i>Antenna type 1</i>
Manufacturer	LABEL ITALY
Antenna model	BKK_2V PANEL VHF WB
Band start(MHz)	174
Band stop(MHz)	225
diagrams Frequency(MHz)	200
Polariz (H,V,C,X)	V
Vertical dist (cm)	150
Height (cm)	87
Width (cm)	125
Thickness (cm)	40
Weight (Kg)	25
Maximum power (KW)	2
Gain (dBd)	7.5
North E.C. (cm)	0
East E.C. (cm)	0
Return loss (dB)	24
R.C.Phase (°)	0

TX station: 6xBkk2-v
Frequency: 200.00 MHz
Gain solid integration : disabled

Site Name: Labelitaly


Geometr. and electrical data of Antenna System

	<i>Power</i> <i>(%)</i>	<i>Tilt</i> <i>(°)</i>	<i>Az.</i> <i>(°/N)</i>	<i>Phase</i> <i>(°)</i>	<i>V dist.</i> <i>(m)</i>	<i>Scr-d</i> <i>(cm)</i>	<i>Scr-Az</i> <i>(°/N)</i>	<i>Rot.</i> <i>(1÷4)</i>	<i>Type</i> <i>(1÷2)</i>	<i>L cables</i> <i>(cm)</i>	<i>Car. phase</i> <i>(°)</i>
1	16.667	0	0	0 +0.0	3.25	0.0	0.0	1	1	300.0	0.0
2	16.667	0	0	0 +0.0	1.95	0.0	0.0	1	1	300.0	0.0
3	16.667	0	0	0 +0.0	0.65	0.0	0.0	1	1	300.0	0.0
4	16.667	0	0	0 +0.0	-0.65	0.0	0.0	1	1	300.0	0.0
5	16.667	0	0	0 +0.0	-1.95	0.0	0.0	1	1	300.0	0.0
6	16.667	0	0	0 +0.0	-3.25	0.0	0.0	1	1	300.0	0.0

TX station: 6xBkk2-v
Frequency: 200.00 MHz
Gain solid integration : disabled

Site Name: Labelitaly

Plan of antenna system



Side of antenna system



TX station: 6xBkk2-v
Frequency: 200.00 MHz
Gain solid integration : disabled

Site Name: Labelitaly

Antennas arrays data

A. Antennas array azimuth (°/N)	0
B. Number of antennas	6
C. Nominal power supply (W)	1000.00
D. Losses (addit. + cables) (dB)	0.0
E. Effective power supply (W)	1000.00
F. Theor. maximum gain (dBd)	15.28
G. Distribution losses (dB)	0.00
H. Nominal max gain [F - G] (dBd)	15.28
I. Compensation losses (dB)	0.00
J. Effec. max gain [H - I] (dBd)	15.28
K. Effec. max gain (times)	33.74
L. Effec. max power [E * K] (KW)	33.7406
M. Max power depr. angle (°)	0.0
N. Max power az. angle (°)	0


Diagram in dBK calculated at horizon

Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK
0	15.3	90	-4.7	180	-4.7	270	-4.7
10	14.9	100	-4.7	190	-4.7	280	-4.7
20	13.8	110	-4.7	200	-4.7	290	-3.1
30	12.1	120	-4.7	210	-4.7	300	1.3
40	9.3	130	-4.7	220	-4.7	310	5.7
50	5.7	140	-4.7	230	-4.7	320	9.3
60	1.3	150	-4.7	240	-4.7	330	12.1
70	-3.1	160	-4.7	250	-4.7	340	13.8
80	-4.7	170	-4.7	260	-4.7	350	14.9

TX station: 6xBkk2-v
Frequency: 200.00 MHz
Gain solid integration : disabled

Site Name: Labelitaly

Horizontal diagram at 0.0° depres. (Total Antenna)




0.0° depres. (Total Antenna), Gain (dBd): 15.28

ERP T.Max(KW): 33.7406 ERP E.Max(KW): 33.7406

TX station: 6xBkk2-v
Frequency: 200.00 MHz
Gain solid integration : disabled

Site Name: Labelitaly

Vertical diagram at an azimuth of 0.0° degrees



0.0° Az. (Total Antenna), Gain (dBd): 15.28

ERP T.Max(KW): 33.7406 ERP E.Max(KW): 33.7406