

TX station: 6xAkl5
Gain solid integration : enabled

Site Name: Labelitaly

General data of Antenna System

TX station	6xAkl5
Site Name	Labelitaly
System of coordinates	Geographic
Longitude	00°00'00.000"
Latitude	00°00'00.000"
Ground level a.s.l. (m)	100.0
Antenna system height (m)	50.0
Transmitter power(Watt)	1000.000
Carrier wave frequency (MHz)	98.000
Antenna system central frequency (MHz)	98.000
Antenna base diagrams type 1	LABEL ITALY-AKL_5 LOG 5 ELEM. FM WB
Antenna base diagrams type 2	-
Polarization (H/V/C/X)	C
Transmitting cable attenuation (dB)	0.0
Additional attenuations(dB)	0.0
Base diagrams sectors (T = All, F = Front)	T
Velocity factor of cables to Antennas (0÷1)	0.88
Coordinate System(C = cartesian, P = polar)	P
Mast side / diameter(cm):	10.0
Mast cross section (T/Q/C)	C
Structure rotation w.r.t. North (°)	0.0
Mast rotation w.r.t. North (°)	0.0

Information about antennas used in the System

	<i>Antenna type 1</i>
Manufacturer	LABEL ITALY
Antenna model	AKL_5 LOG 5 ELEM.
Band start(MHz)	88
Band stop(MHz)	108
diagrams Frequency(MHz)	98
Polariz (H,V,C,X)	V
Vertical dist (cm)	260
Height (cm)	173
Width (cm)	6
Thickness (cm)	143
Weight (Kg)	4.5
Maximum power (KW)	2
Gain (dBd)	6.2
North E.C. (cm)	0
East E.C. (cm)	0
Return loss (dB)	20
R.C.Phase (°)	0

TX station: 6xAkl5
Frequency: 98.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly


Geometr. and electrical data of Antenna System

	<i>Power</i> <i>(%)</i>	<i>Tilt</i> <i>(°)</i>	<i>Az.</i> <i>(°/N)</i>	<i>Phase</i> <i>(°)</i>	<i>V dist.</i> <i>(m)</i>	<i>Scr-d</i> <i>(cm)</i>	<i>Scr-Az</i> <i>(°/N)</i>	<i>Rot.</i> <i>(1÷4)</i>	<i>Type</i> <i>(1÷2)</i>	<i>L cables</i> <i>(cm)</i>	<i>Car. phase</i> <i>(°)</i>
1	16.667	0	0	0 +0.0	6.50	0.0	0.0	1	1	0.0	0.0
2	16.667	0	0	0 +0.0	3.90	0.0	0.0	1	1	0.0	0.0
3	16.667	0	0	0 +0.0	1.30	0.0	0.0	1	1	0.0	0.0
4	16.667	0	0	0 +0.0	-1.30	0.0	0.0	1	1	0.0	0.0
5	16.667	0	0	0 +0.0	-3.90	0.0	0.0	1	1	0.0	0.0
6	16.667	0	0	0 +0.0	-6.50	0.0	0.0	1	1	0.0	0.0

TX station: 6xAkl5
Frequency: 98.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly

Plan of antenna system



Side of antenna system



TX station: 6xAkl5
Frequency: 98.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly

Antennas arrays data

A. Antennas array azimuth (°/N)	0
B. Number of antennas	6
C. Nominal power supply (W)	1000.00
D. Losses (addit. + cables) (dB)	0.0
E. Effective power supply (W)	1000.00
F. Theor. maximum gain (dBd)	13.11
G. Distribution losses (dB)	0.00
H. Nominal max gain [F - G] (dBd)	13.11
I. Compensation losses (dB)	0.00
J. Effec. max gain [H - I] (dBd)	13.11
K. Effec. max gain (times)	20.46
L. Effec. max power [E * K] (KW)	20.4595
M. Max power depr. angle (°)	0.0
N. Max power az. angle (°)	0

Diagram in dBK calculated at horizon


Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK
0	13.1	90	3.2	180	-6.9	270	3.2
10	13.0	100	0.7	190	-6.9	280	5.4
20	12.7	110	-2.4	200	-6.9	290	7.5
30	12.3	120	-5.4	210	-6.9	300	9.4
40	11.6	130	-6.9	220	-6.9	310	10.6
50	10.6	140	-6.9	230	-6.9	320	11.6
60	9.4	150	-6.9	240	-5.4	330	12.3
70	7.5	160	-6.9	250	-2.4	340	12.7
80	5.4	170	-6.9	260	0.7	350	13.0

TX station: 6xAkl5

Frequency: 98.00 MHz

Gain solid integration : enabled

Site Name: Labelitaly

Horizontal diagram at 0.0° depres. (Total Antenna)


— 0.0° depres. (Total Antenna), Gain (dBd): 13.11

ERP T.Max(KW): 20.4595 ERP E.Max(KW): 20.4595

TX station: 6xAkl5
 Frequency: 98.00 MHz
 Gain solid integration : enabled

Site Name: Labelitaly

Vertical diagram at an azimuth of 0.0° degrees



0.0° Az. (Total Antenna), Gain (dBd): 13.11

ERP T.Max(KW): 20.4595 ERP E.Max(KW): 20.4595