

TX station: 3xBkk2-h
Gain solid integration : enabled

Site Name: Labelitaly

General data of Antenna System

TX station	3xBkk2-h
Site Name	Labelitaly
System of coordinates	Geographic
Longitude	00°00'00.000"
Latitude	00°00'00.000"
Ground level a.s.l. (m)	100.0
Antenna system height (m)	50.0
Transmitter power(Watt)	1000.000
Carrier wave frequency (MHz)	200.000
Antenna system central frequency (MHz)	200.000
Antenna base diagrams type 1	LABEL ITALY-BKK_2V PANEL VHF WB
Antenna base diagrams type 2	-
Polarization (H/V/C/X)	H
Transmitting cable attenuation (dB)	0.0
Additional attenuations(dB)	0.0
Base diagrams sectors (T = All, F = Front)	T
Velocity factor of cables to Antennas (0÷1)	0.88
Coordinate System(C = cartesian, P = polar)	P
Mast side / diameter(cm):	10.0
Mast cross section (T/Q/C)	C
Structure rotation w.r.t. North (°)	0.0
Mast rotation w.r.t. North (°)	0.0

Information about antennas used in the System

	<i>Antenna type 1</i>
Manufacturer	LABEL ITALY
Antenna model	BKK_2V PANEL VHF WB
Band start(MHz)	174
Band stop(MHz)	225
diagrams Frequency(MHz)	200
Polariz (H,V,C,X)	V
Vertical dist (cm)	150
Height (cm)	87
Width (cm)	125
Thickness (cm)	40
Weight (Kg)	25
Maximum power (KW)	2
Gain (dBd)	7.5
North E.C. (cm)	0
East E.C. (cm)	0
Return loss (dB)	24
R.C.Phase (°)	0

TX station: 3xBkk2-h
Frequency: 200.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly


Geometr. and electrical data of Antenna System

	<i>Power</i> (%)	<i>Tilt</i> (°)	<i>Az.</i> (°/N)	<i>Phase</i> (°)	<i>V dist.</i> (m)	<i>Scr-d</i> (cm)	<i>Scr-Az</i> (°/N)	<i>Rot.</i> (1÷4)	<i>Type</i> (1÷2)	<i>L cables</i> (cm)	<i>Car. phase</i> (°)
1	33.333	0	0	0 +0.0	1.40	0.0	0.0	2	1	0.0	0.0
2	33.333	0	0	0 +0.0	0.00	0.0	0.0	2	1	0.0	0.0
3	33.333	0	0	0 +0.0	-1.40	0.0	0.0	2	1	0.0	0.0

TX station: 3xBkk2-h
Frequency: 200.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly

Plan of antenna system



Side of antenna system

* = rotated antenna



TX station: 3xBkk2-h
Frequency: 200.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly

Antennas arrays data

A. Antennas array azimuth (°/N)	0
B. Number of antennas	3
C. Nominal power supply (W)	1000.00
D. Losses (addit. + cables) (dB)	0.0
E. Effective power supply (W)	1000.00
F. Theor. maximum gain (dBd)	12.24
G. Distribution losses (dB)	0.00
H. Nominal max gain [F - G] (dBd)	12.24
I. Compensation losses (dB)	0.00
J. Effec. max gain [H - I] (dBd)	12.24
K. Effec. max gain (times)	16.76
L. Effec. max power [E * K] (KW)	16.7577
M. Max power depr. angle (°)	0.0
N. Max power az. angle (°)	0


Diagram in dBK calculated at horizon

Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK
0	12.2	90	-7.8	180	-7.8	270	-7.8
10	12.1	100	-7.8	190	-7.8	280	-7.8
20	11.4	110	-6.7	200	-7.8	290	-1.7
30	10.2	120	-6.6	210	-7.8	300	2.6
40	8.5	130	-7.4	220	-7.8	310	6.2
50	6.2	140	-7.8	230	-7.4	320	8.5
60	2.6	150	-7.8	240	-6.6	330	10.2
70	-1.7	160	-7.8	250	-6.7	340	11.4
80	-7.8	170	-7.8	260	-7.8	350	12.1

TX station: 3xBkk2-h
Frequency: 200.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly

Horizontal diagram at 0.0° depres. (Total Antenna)




0.0° depres. (Total Antenna), Gain (dBd): 12.24

ERP T.Max(KW): 16.7577 ERP E.Max(KW): 16.7577

TX station: 3xBkk2-h
Frequency: 200.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly

Vertical diagram at an azimuth of 0.0° degrees



0.0° Az. (Total Antenna), Gain (dBd): 12.24

ERP T.Max(KW): 16.7577 ERP E.Max(KW): 16.7577