

TX station: 12xAkk2
Gain solid integration : enabled

Site Name: Labelitaly

General data of Antenna System

TX station	12xAkk2
Site Name	Labelitaly
System of coordinates	Geographic
Longitude	00°00'00.000"
Latitude	00°00'00.000"
Ground level a.s.l. (m)	100.0
Antenna system height (m)	50.0
Transmitter power(Watt)	1000.000
Carrier wave frequency (MHz)	98.000
Antenna system central frequency (MHz)	98.000
Antenna base diagrams type 1	LABEL ITALY-AKK_2V PANEL W.B. FM vertical pol.
Antenna base diagrams type 2	-
Polarization (H/V/C/X)	V
Transmitting cable attenuation (dB)	0.0
Additional attenuations(dB)	0.0
Base diagrams sectors (T = All, F = Front)	T
Velocity factor of cables to Antennas (0÷1)	0.88
Coordinate System(C = cartesian, P = polar)	P
Mast side / diameter(cm):	10.0
Mast cross section (T/Q/C)	C
Structure rotation w.r.t. North (°)	0.0
Mast rotation w.r.t. North (°)	0.0

Information about antennas used in the System

	<i>Antenna type 1</i>
Manufacturer	LABEL ITALY
Antenna model	AKK_2V PANEL W.B. F
Band start(MHz)	88
Band stop(MHz)	105
diagrams Frequency(MHz)	98
Polariz (H,V,C,X)	V
Vertical dist (cm)	310
Height (cm)	174
Width (cm)	248
Thickness (cm)	80
Weight (Kg)	45
Maximum power (KW)	5
Gain (dBd)	8.1
North E.C. (cm)	0
East E.C. (cm)	0
Return loss (dB)	0
R.C.Phase (°)	0

TX station: 12xAkk2
Frequency: 98.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly


Geometr. and electrical data of Antenna System

	<i>Power</i> (%)	<i>Tilt</i> (°)	<i>Az.</i> (°/N)	<i>Phase</i> (°)	<i>V dist.</i> (m)	<i>Scr-d</i> (cm)	<i>Scr-Az</i> (°/N)	<i>Rot.</i> (1÷4)	<i>Type</i> (1÷2)	<i>L cables</i> (cm)	<i>Car. phase</i> (°)
1	10.000	0	0	0 +0.0	12.60	0.0	0.0	1	1	0.0	0.0
2	10.000	0	0	0 +0.0	9.80	0.0	0.0	1	1	0.0	0.0
3	10.000	0	0	0 +0.0	7.00	0.0	0.0	1	1	0.0	0.0
4	10.000	0	0	0 +0.0	4.20	0.0	0.0	1	1	0.0	0.0
5	10.000	0	0	0 +0.0	1.40	0.0	0.0	1	1	0.0	0.0
6	10.000	0	0	0 +0.0	-1.40	0.0	0.0	1	1	0.0	0.0
7	10.000	0	0	0 +0.0	-4.20	0.0	0.0	1	1	0.0	0.0
8	10.000	0	0	0 +0.0	-7.00	0.0	0.0	1	1	0.0	0.0
9	10.000	0	0	0 +0.0	-9.80	0.0	0.0	1	1	0.0	0.0
10	10.000	0	0	0 +0.0	-12.60	0.0	0.0	1	1	0.0	0.0

TX station: 12xAkk2
Frequency: 98.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly

Plan of antenna system



Side of antenna system



TX station: 12xAkk2
Frequency: 98.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly

Antennas arrays data

A. Antennas array azimuth (°/N)	0
B. Number of antennas	10
C. Nominal power supply (W)	1000.00
D. Losses (addit. + cables) (dB)	0.0
E. Effective power supply (W)	1000.00
F. Theor. maximum gain (dBd)	18.00
G. Distribution losses (dB)	0.00
H. Nominal max gain [F - G] (dBd)	18.00
I. Compensation losses (dB)	0.00
J. Effec. max gain [H - I] (dBd)	18.00
K. Effec. max gain (times)	63.05
L. Effec. max power [E * K] (KW)	63.0530
M. Max power depr. angle (°)	0.0
N. Max power az. angle (°)	358


Diagram in dBK calculated at horizon

Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK	Az. (°/N)	dBK
0	18.0	90	-2.0	180	-2.0	270	-2.0
10	17.6	100	-2.0	190	-2.0	280	-2.0
20	16.7	110	-2.0	200	-2.0	290	0.9
30	15.0	120	-2.0	210	-2.0	300	4.8
40	11.8	130	-2.0	220	-2.0	310	8.6
50	8.6	140	-2.0	230	-2.0	320	11.8
60	4.8	150	-2.0	240	-2.0	330	15.0
70	0.9	160	-2.0	250	-2.0	340	16.7
80	-2.0	170	-2.0	260	-2.0	350	17.6

TX station: 12xAkk2
Frequency: 98.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly

Horizontal diagram at 0.0° depres. (Total Antenna)




0.0° depres. (Total Antenna), Gain (dBd): 18 ERP T.Max(KW): 63.0531 ERP E.Max(KW): 63.0531

TX station: 12xAkk2
Frequency: 98.00 MHz
Gain solid integration : enabled

Site Name: Labelitaly

Vertical diagram at an azimuth of 0.0° degrees



0.0° Az. (Total Antenna), Gain (dBd): 18

ERP T.Max(KW): 63.0531 ERP E.Max(KW): 63.0531